

INTERNATIONAL FLYING FIFTEEN CLASS

MEASUREMENT FORM

Authority: * WORLD SAILING, P O Box 95, 2a Lord Street, Douglas, Isle of Man, IM99 1HP, United Kingdom

IN ORDER TO OBTAIN A MEASUREMENT CERTIFICATE

- 1. The builder shall pay the International Class Fee to the National Flying Fifteen Association, who will issue an official International Class Fee Receipt and a sail number.
2. The boat shall be measured by an Official Measurer or Measurers in accordance with Class Rule A3, who shall complete and sign this measurement form.
3. The Measurement Form, when completed, shall be sent to the owner's Certification Authority (see Class Rule A1) together with the International Class Fee Receipt and any registration fee which may be required.

BEFORE SUBMITTING THIS FORM MAKE SURE IT HAS BEEN PROPERLY COMPLETED

BOAT SAIL NUMBER

BOAT NAME

DATE BUILT DATE MEASUREMENT COMPLETED

OWNER'S DECLARATION

Name of Owner

Address

Owner's Club (see Racing Rule 75)

Signed: Date:

[Disclaimer: The owner acknowledges that this document may be shared with third parties within the Federation of Flying Fifteen International]

* WORLD SAILING is not a National Authority as referred to in the Class Rules.

NOTE: All measurements are in millimetres unless otherwise stated

Item No	Rule No	Measurement	Minimum	Actual	Maximum
		<u>HULL</u>			
1	B4	Is transom flat and vertical to the base line		Yes/No	
2	B4	Is the radius between the transom and hull skin less than 13mm		Yes/No	
3	B4	Base line to centreplane at transom		381	
4	B4	Base line to centreplane at Station 8 (737mm from HDP)	300		315
5	B4	Base line to centreplane at Station 6 (2261mm from HDP)	168		183
6	B4	Base line to centreplane at Station 4 (3785mm from HDP)	134		149
7	B4	Base line to centreplane at Station 3 (4547mm from HDP)	165		180
8	B4	Base line to centreplane at Station 2 (5311mm from HDP)		305	
9	B4	Base line to centreplane at Station 1 (5613mm from HDP)	407		419
10	B4	Base line to sheerline at stem head	825		876
11	B4	Boat length overall including any stem head fittings	6046		6096
		<u>Hull Sections</u>		Port	Stbd
		<u>Transom</u>			
12	B4	Clearance between hull and template	0		15
13	B4	Beam at sheerline from template	72		85
		<u>Station 8</u>			
14	B4	Clearance between hull and template	0	Yes/No	15
		(a) at 1B	0		15
		(b) at 1LL	0		15
		(c) at 2LL	0		15
15	B4	Sheerline below top of template	0		35
16	B4	Beam at sheerline from template	76		90
		<u>Station 6</u>		Port	Stbd
17	B4	Base line to hull at 635mm from centreplane	315		330
18	B4	Clearance between hull and template	0	Yes/No	15
		(a) at LWL	0		15
		(b) at 1LL	0		15
		(c) at 2LL	0		15
19	B4	Sheerline below top of template	0		25
20	B4	Beam at sheerline from template	76		89

Item No	Rule No	Measurement	Minimum	Actual	Maximum
		<u>Station 4</u>			
21	B4	Base line to hull at 483mm from centreplane	315		330
22	B4	Clearance between hull and template	0	Yes/No	15
		(a) at 1B	0		15
		(b) at LWL	0		15
		(c) at 1LL	0		15
		(d) at 2LL	0		15
		(e) at 3LL	0		15
23	B4	Sheerline below top of template	0		40
24	B4	Beam at sheerline from template	76		89
		<u>Station 3</u>			
25	B4	Clearance between hull and template	0	Yes/No	15
		(a) at LWL	0		15
		(b) at 1LL	0		15
		(c) at 2LL	0		15
		(d) at 3LL	0		15
26	B4	Sheerline below top of template	0		30
27	B4	Beam at sheerline from template	77		90
		<u>Station 2</u>			
28	B4	Clearance between hull and template	0	Yes/No	15
		(a) at 1LL	0		15
		(b) at 2LL	0		15
		(c) at 3LL	0		15
29	B4	Sheerline below top of template	0		30
30	B4	Beam at sheerline from template	80		94
31	B1	Are the sections of the hull fair at and between stations		Yes/No	
32	B4	Profile of bow between station 2 & stem is a fair curve		Yes/No	
33	B2	Hull & transom weight/unit area greater than 3.2 kg/m ²		Yes/No	
		<u>DECK & COCKPIT</u>			
34	B4	Plan width of side deck and bulkhead assembly from sheerline	356		
35	B4	Side deck and bulkhead assembly is above the sheerline within 280mm of sheerline		Yes/No	
36	B4	Camber of fore and aft decks			150
37	B4	Athwartships sections of fore and aft decks are a fair curve from sheerline to sheerline		Yes/No	
38	B4	Combined height of deck and breakwater			
		(a) at centreplane	175		
		(b) at 25mm from sheerline	25		

Item No	Rule No	Measurement	Minimum	Actual	Maximum
39	B4	Is the breakwater a fair convex curve from the centreplane to within 25mm of sheerline		Yes/No	
40	B2	Plan width of rubbing strakes (if fitted) from sheerline			76
41	B2	Depth of rubbing strakes from sheerline			60
42	B4	Outboard edge of spinnaker pockets (if fitted) to sheerline	280		
43	B4	Is spinnaker chute (if fitted) forward of Station 2		Yes/No	
44	B4	Does spinnaker chute or pockets drain to cockpit or overboard		Yes/No	
45	B7	Distance from transom to point at which the centreline of the rudder stock intersects aft deck	470		736
46	B4	Aft edge of cockpit from transom	1540		1830
47	B4	Forward edge of cockpit (excluding mast slot) from transom	3630		3780
48	B4	Foremost edge of breakwater from transom			4475
49	B4	Plan width of cockpit floor aft of shrouds	600		
50	B12	Distance between points of intersection of shrouds with deck or rubbing strake	1270		
51	B12	Distance shrouds intersect rubbing strakes outside sheerline			45
52	B4	Floor watertight compartments (if fitted)			
		(a) Distance below sheerline	300		
		(b) Width of channel in way of the keel flange	140		
		(c) Does the channel extend the full length of the keel flange		Yes/No	
		(d) Floor of the channel if an internal moulding – correctly bonded		Yes/No	
		(e) Are self-bailers correctly fitted (not through internal mouldings)		Yes/No	
53	B14	No more than 4 self-bailers effective area 650mm ² each		Yes/No	
54	B2	Deck weight/unit area greater than 3.2 kg/m ²		Yes/No	
55	B4	Is a stainless steel towing fairlead fitted (25mm x 4mm) within 700mm of stem head		Yes/No	
56	B12	Are outriggers (if used) through the rubbing strakes and not less than 15mm from the outer edge of the rubbing strakes		Yes/No	
57	B5	Is hull constructed with “watertight” compartments (min. 4)		Yes/No	
58	B5	Is removable buoyancy fitted in compliance with Rule B5 (443 kg total, 100 kg forward, 1-130 kg per unit)		Yes/No	
		Type of buoyancy No. of units			
59	B3	Sail number cut, stamped, branded or moulded in hog in figures not less than 25mm in height		Yes/No	
60	B17	Builder's mark within 150 x 150mm square		Yes/No	

Item No	Rule No	Measurement	Minimum	Actual	Maximum
		<u>WEIGHT</u>			
61	B8	Hull weight (including removable buoyancy & hatch covers)		kg	
62	B8	Total weight of correctors (if fitted) through fastened and visible within cockpit.		kg	16 kg
63	B8	Individual corrector weights (kg) 1.....2.....3.....4.....			
64	B8	Total hull weight including corrector weight (items 61 + 62)	133 kg	kg	
65	B6	Finished keel weight (including bolts or studs)	169 kg	kg	193 kg
66	B7	Finished rudder and stock weight	3.8 kg	kg	
		<u>KEEL</u>			
67	B6	Clearance of keel profile template from keel			13
68	B6	Clearance of athwartships keel templates from keel			5
69	B6	Concavity of sections parallel to the baseline			1
70	B6	Maximum athwartships dimensions of finished keel			
		(a) in an area between 300mm and 500mm above the profile template baseline	32		42
		(b) in an area between 500mm above the profile template baseline and 30mm below the top of the flange			50
71	B6	Width of finished keel flange	124		136
72	B6	Thickness of keel flange 10mm from edges	10		
73	B6	Radius of all 4 corners and all 4 edges of keel flange			10
74	B6	Keel bolts/studs and their configuration comply with B6.12		Yes/No	
75	B6	Fore end of keel from hull datum point	3860		4040
		<u>RUDDER</u>			
76	B7	Clearance of rudder template from rudder			13
77	B7	Thickness of rudder at any point			45
78	B7	Rudder stock			
		(a) solid stainless steel of diameter, or	18		
		(b) solid bronze of diameter , or	23		
		(c) stainless steel tube of outside diameter (min. wall thickness 2.5mm)	25		
79	B7	Fore end of rudder from hull datum point	710		762
80	B7	Variation in gap between rudder and hull at the centreplane			5
		<u>SPARS RIGGING AND FITTINGS</u>			
81	B11	Mast spar and main boom spar of wood or aluminium alloy		Yes/No	
82	B12	Spreaders of aluminium alloy		Yes/No	
83	B9	Mean mast spar dimensions below limit mark No. 3 and 300mm above limit mark No. 2			
		(a) fore and aft = mm			
		(b) athwartships = mm			
		(a + b) =mm			
			60		80
					2

Item No	Rule No	Measurement	Minimum	Actual	Maximum
84	B9	Is upper edge of limit mark No.4 (mast datum point) at or below sheerline with the mast in the vertical position.		Yes/No	
85	B9	Heel point of mast from upper edge of limit mark No.4	450		
86	B9	Lower edge of limit mark No. 1 above upper edge of limit mark No. 4			6860
87	B9	Lower edge of limit mark No. 3 above upper edge of limit mark No. 4			4724
88	B9	Upper edge of limit mark No. 2 below lower edge of limit mark No. 1			6248
89	B12	Headsail luff, or its extension meets the mast at or below lower edge of limit mark No. 3		Yes/No	
90	B12	Forestay (if fitted) or its extension meets the mast between Headsail luff and 80mm above limit mark No. 3		Yes/No	
91	B12	Distance shrouds intersect mast above limit mark No. 3			150
92	B12	Distance of point where extension of spinnaker halyard when held at right angles to mast meets foreside of mast above lower edge of limit mark No. 3			102
93	B12	Extension of spinnaker halyard eye or block (if fitted) from foreside of mast			76
94	B12	Point forestay (if fitted) meets deck forward of headsail luff	5		280
95	B12	Diameter of standing rigging	2.3		
96	B9	Projection of spinnaker boom fitting(s) from mast			50
97	B9	Aft side of mast to pivot point of gooseneck			40
98	B9	Mast weight including normal permanent fittings and rigging	10.5 kg		
99	B9	Centre of gravity of mast in same condition as for weighing above upper edge of limit mark No. 2	1828		
100	B9	Mast spar deflection			145
101	B9	Mast spar curvature between limit marks Nos. 1 and 2			50
102	B10	Foreside of mast spar at deck level between 3695mm and 3850mm from aft edge of transom (measured horizontally)		Yes/No	
103	B10	Foreside of mast spar to point where line of headsail luff or its extension meet the deck			1676
104	B10	Foreside of mast spar to point of intersection of shrouds, or extension of line of shrouds, with deck or rubbing strake	520		
105	B10	Does the mast gate control aft movement of the mast to the limits of items 102, 103 and 104		Yes/No	
106	B10	Height of control of mast movement above deck			50
107	B11	Is boom, including sail track able to pass through 125mm circle		Yes/No	
108	B11	Upper edge of boom intersects mast above limit mark No.2		Yes/No	
109	B11	Aft side of mast to boom outer limit mark			3000
110	B11	Boom spar curvature			10

Item No	Rule No	Measurement	Minimum	Actual	Maximum
111	B11	Overall length of spinnaker pole spar(s) including fittings and items that are part of the spinnaker pole(s)			2000
112	B13	Headsail tack point not less than 100mm above deck (measured along line of luff)		Yes/No	
<u>EQUIPMENT & MISCELLANEOUS</u>					
113	B15	Anchor, chain and line comply with Rule B15.3 (2 kg min, 18m x 6mm line)		Yes/No	
114	B15	Paddle (1000mm, 0.4 kg min.)		Yes/No	
115	B15	Two bailers (each 1 litre min.), or bailer and pump		Yes/No	
116	B14	Does compass comply with Rule B14.4		Yes/No	
117	B14	Do cameras/trackers (if fitted) comply with Rule B14.4		Yes/No	
118	A2	World Sailing plaque fixed in a visible position		Yes/No	
119	B14	Hiking straps or hobbles (if fitted) comply with Rule B14.1		Yes/No	
120	B17	Does hull and spar advertising comply with Rule B17		Yes/No	

BUILDER'S DECLARATION

To be completed by the builder of the hull.

I certify that the International Class Fee has been paid in respect of the hull and that the following sail number has been allocated.

Name of Builder:

Address:
.....
.....

Date Built: Sail Number

Construction Materials

Hull ShellDecks

If of GRP

Mould No.Serial No.

I certify that this boat has been constructed in accordance with the Rules of the International Flying Fifteen Class.

Signed: Date:

MEASURER'S DECLARATION

To be completed by a Measurer or Measurers in accordance with Class Rule A3.

I declare that I have measured the above boat and that it complies to the best of my knowledge in every respect with the Class Rules except as stated under measurer's remarks.

a) **Hull and Appendages** Item Nos (1 – 80)

Name of Measurer: Approved by:

Address:

.....

Signed: Date: :

b) **Rig and Other Items** Item Nos (81 – 120)

Name of Measurer: Approved by:

Address:

.....

Signed: Date: :

MEASURER'S REMARKS

DATE ORIGINAL MEASUREMENT COMPLETED:

OFFICIAL FLYING FIFTEEN CLASS MEASURER'S DECLARATION:

"In accordance with Class Rule A3, I declare that satisfactory measurement of the above boat has been completed."

Signed: Date:

Effective:	1 March 2022
Previous Issues	1 March 2020
	1 March 2017
	1 March 2014
	1 March 2011
	1 March 2008
	1 December 2004
	1 March 2002
	1 March 2001

INTERNATIONAL FLYING FIFTEEN CLASS

SAIL MEASUREMENT FORM

NAME OF BOAT SAIL NUMBER

OWNER

Item No	Rule No	Measurement	Minimum	Actual	Maximum
		<u>MAINSAIL</u>			
		Maker's Name:			
		Serial No.:			
		Measurement Date:			
121	B13	Top width			130
122	B13	Headboard width measured at right angles to the luff			102
123	B13	Leech length			6530
124	B13	Half width			2015
125	B13	Three-quarter width			1150
126	B13	Head point to intersection of leech and centreline of upper most batten pocket	1250		
127	B13	Batten pocket distances, measured between the intersections of the pocket centrelines and the leech	1200		
128	B13	Clew point to intersection of leech and centreline of lower most batten pocket	1250		
129	B13	Batten pockets			
		(a) upper pocket inside length			782
		(b) other pockets inside length			1035
		(c) inside width			60
		(d) closed at luff end		Yes/No	
130	B13	Primary reinforcement			340
131	B13	Secondary reinforcement			
		(a) from sail corner measurement points			1020
		(b) for flutter patches			140
		(c) for chafing patches			1020
		(d) for batten pocket patches			175
132	B13	Tabling width			40
133	B13	Seam width			20
134	B13	Windows, not exceeding 3, max. total area of 0.6m ²		Yes/No	
135	B13	Window to sail edge	150		
136	B13	Inner end of foot bolt rope from clew point	2500		

Item No	Rule No	Measurement	Minimum	Actual	Maximum
137	B13	Does upper leech shape conform to B13.5.1(d)		Yes/No	
138	B13	Do distinguishing numbers, and letters (height 300mm, spacing 60mm) and Class emblem comply with Class Rules and RRS Rule 77		Yes/No	
139	B17	Sailmaker's mark max. 150 x 150mm within 450mm of tack		Yes/No	
		<u>HEADSAIL</u>			
		Maker's Name:			
		Serial No:			
		Measurement Date:			
140	B13	Top width			40
141	B13	Luff length	4390		4420
142	B13	Leech length			4090
143	B13	Foot median			4265
144	B13	Foot length			2180
145	B13	Foot irregularity			35
146	B13	Primary reinforcement			275
147	B13	Secondary reinforcement			
		(a) from sail corner measurement points			825
		(b) for flutter patches			100
		(c) for chafing patches			825
148	B13	Tabling width			40
149	B13	Seam width			20
150	B13	Windows, max. total area of 0.3m ²		Yes/No	
151	B13	Window to sail edge	150		
152	B13	Does leech shape conform to B13.6.1(c)		Yes/No	
153	B17	Sailmaker's mark max. 150 x 150mm within 355mm of tack		Yes/No	
		<u>SPINNAKER</u>			
		Maker's Name:			
		Serial No:			
		Measurement Date:			
154	B13	Is the sail symmetrical		Yes/No	
155	B13	Leech lengths, measured around the leeches			4725
156	B13	Difference between leeches			50
157	B13	Distances from clew points to mid point foot, measured around the foot			1830
158	B13	Distances between points of the leeches 2350mm from the head point (measured around the leeches) and a point on the centre line 2350mm from the head point	1460		1760
159	B13	Foot median			5300

Item No	Rule No	Measurement	Minimum	Actual	Maximum
160	B13	Primary reinforcement			295
161	B13	Secondary reinforcement			
		(a) from sail corner measurement points			885
		(b) from spinnaker recovery patches			350
162	B13	Tabling width			40
163	B13	Seam width			20
164	B13	Do sail numbers (height 300mm, spacing 60mm) comply with RRS Rule 77		Yes/No	
		<u>Sails General</u>			
165	A5	Are all sails that measure signed and dated		Yes/No	
166	B17	Sail advertising complies with Rule B17		Yes/No	

MEASURER'S DECLARATION

To be completed by an Official Flying Fifteen Class Measurer, a Flying Fifteen Class Maintenance Measurer, or an Official Measurer (see Rule A3).

I declare that I have measured the above sail(s) which comply to the best of my knowledge in every respect with the Class Rules.

Sails Item Nos (121 – 166)

Name of Measurer: Approved by:

Address:

.....

Signed: Date:

Effective: 1 March 2022

Previous Issues: 1 March 2020
1 March 2017
1 March 2014
1 March 2011
1 December 2008
1 March 2004
1 March 2002
1 March 2001